UV Dynamics®
defining UV innovation

315 Neptune Crescent, London, Ontario, Canada
Phone: +1 519 452 7520 | Email:
info@uvdynamics.com
Website: www.uvdynamics.com



UVD485

ultraviolet water disinfection system

KEY FEATURES

- Easy-service lamp connector simplifies maintenance - no tools required.
- Microprocessor controlled power source includes audible and visible lamp failure alarms, lamp life remaining feature, and annual lamp change timer.
- UV lamps are USA manufactured with a long-life coating; rated for 9,000hrs.
- Disinfection chambers are welded in Canada using 304 stainless steel.
- Power sources and chambers are designed and manufactured in Canada.
- **Available in 3 models to suit varying system requirements:**
  UVD485E: basic model
  UVD485: + solenoid compatible
  UVD485/S: + UV intensity monitor (calibrated at 40mJ/cm²)

OVERVIEW

The UVD485 is applicable to point of entry applications in today's larger homes and cottages. The 30mJ/cm² dose of the *UVD485* at 16gpm is ideal for general disinfection. The compact mounting footprint facilitates installations where space is limited.

The *UVD485* system was designed using sophisticated computer modeling software, and then verified by independent third-party testing using accepted biodosimetry methods by GAP EnviroMicrobial Services.

PRODUCT SPECIFICATIONS

Flow Rate - 16mJ/cm²:	30gpm (113L) (6.8m³/hr)
- 30mJ/cm²:	16gpm (60L) (3.6m³/hr)
- 40mJ/cm²:	12gpm (45L) (2.7m³/hr)
Shipping Weight:	9lbs
Chamber Dimensions:	24.25" (62cm) x 3.5" (9cm)

Inlet/Outlet Port Size:	1"MNPT
Max Operating Pressure:	100psi (6.9bar)
Water Temperature:	4 - 37°C (40-99°F)
Power Consumption:	63 watts
AC Supply Voltage:	120V or 240V (47-63Hz)

* 16mJ/cm² dose is suitable for reducing non-pathogenic nuisance organisms only.
Disinfection chamber hydraulic performance may limit maximum flow rate.
Specified flow rates assume input water with 95% UVT
† Chamber dimensions do not include side ports or maintenance headroom. For dimensional drawings, please contact the factory.

THE WARRANTY

UVDynamics water disinfection systems are supported with a 'free from defects' Workmanship and Material warranty:

- Ten year prorated warranty on the stainless steel disinfection chamber
- Three year warranty on the UV power source
- One year warranty on UV lamps, sleeves, sensor, and solenoid

conditions apply, contact manufacturer for details

IAPMO R&T WATER QUALITY PLATINUM SEAL IAPMO RESEARCH AND TESTING®

UPC C ®

C ETL LISTED Intertek

Systems* tested and certified by IAPMO against:
NSF/ANSI 61 (materials safety only)
NSF/ANSI 372 (lead free compliance)
CSA-B483.1

*visit iapmo.org for model information

© COPYRIGHT 2024 – All Rights Reserved -UVDynamics - a Castle Circuits Inc Business Group