315 Neptune Crescent, London, Ontario, Canada
Phone: +1 519 452 7520 | Email: info@uvdynamics.com
Website: www.uvdynamics.com



UVD1500

ultraviolet water disinfection system

KEY FEATURES

- Easy-service lamp connector simplifies maintenance - no tools required.
- Microprocessor controlled power source includes audible and visible lamp failure alarms, lamp life remaining feature, and annual lamp change timer.
- UV lamps are USA manufactured with a long-life coating; rated for 9,000hrs.
- Disinfection chambers are welded in Canada using 304 stainless steel.
- Power sources and chambers are designed and manufactured in Canada.
- Solenoid valve compatibility for automatic shut-off during alarm conditions.
- Optional model available: UVD1500/S with UV intensity monitor (Calibrated at 40 mJ/cm^2) .

OVERVIEW

The UVDynamics model UVD1500 is applicable for general disinfection in smaller commercial / industrial applications. The 30mJ/cm^2 dose of the *UVD1500* at 50gpm is ideal for general disinfection.

The *UVD1500* system was designed using sophisticated computer modeling software, and then verified by independent third-party testing using accepted biodosimetry methods by GAP EnviroMicrobial Services.

PRODUCT SPECIFICATIONS

Flow Rate - 16mJ/cm^2:	94gpm (356L) (21.4m^3/hr)
- 30mJ/cm^2:	50gpm (189L) (11.3m^3/hr)
- 40mJ/cm^2:	37gpm (140L) (8.4m^3/hr)
Shipping Weight:	20lbs
Chamber Dimensions:	50.5 (128cm) x 4" (10cm)

* 16mJ/cm^2 dose is suitable for reducing non-pathogenic nuisance organisms only.
Disinfection chamber hydraulic performance may limit maximum flow rate.
Specified flow rates assume input water with 95% UVT
† Chamber dimensions do not include side ports or maintenance headroom. For dimensional drawings, please contact the factory.

Inlet/Outlet Port Size:	1¼" MNPT
Max Operating Pressure:	100psi (6.9bar)
Water Temperature:	4 - 37°C (40-99°F)
Power Consumption:	117 watts
AC Supply Voltage:	120V or 240V (47-63Hz)

THE WARRANTY

UVDynamics water disinfection systems are supported with a 'free from defects' Workmanship and Material warranty:

- Ten year prorated warranty on the stainless steel disinfection chamber
- Three year warranty on the UV power source
- One year warranty on UV lamps, sleeves, sensor, and solenoid conditions apply, contact manufacturer for details

Systems* tested and certified by IAPMO against:

NSF/ANSI 61 (materials safety only)
NSF/ANSI 372 (lead free compliance)
CSA-B483.1

*visit iapmo.org for model information

© COPYRIGHT 2024 – All Rights Reserved –UVDynamics – a Castle Circuits Inc Business Group